FUNDER
BY GENESIS PRODUCTS

WHERE BEAUTY, DURABILITY AND FUNCTIONALITY LIVE

PREMIUM TFL CLOSET & SHELVING SOLUTIONS

Funder TFL closet and shelving components meet your stock white requirements while offering an expansive variety of sizes, styles and substrates – all with the durability and performance of thermally-fused laminate (TFL). Beautifully-finished edges and a large assortment of designs, including trending solids and woodgrains, deliver storage that stands up to everyday use.

WE ARE CORE NEUTRAL

This means you can match the TFL surface to the substrate that best fits your core needs.

FLEXIBLE DESIGN OPTIONS

Choose from stock white shelving or create your own. Your budget and vision can seamlessly align with materials – ranging from standard to premium.

INTRODUCING **EVER**PLY™

Our TFL on plywood solution

This proprietary substrate limits warping and swelling from moisture while elevating durability.

WHY TFL?

Thermally-Fused Laminate (TFL) is fused with heat and pressure to a composite core for a strong surface material that offers superior performance.

Durability
Holds up to scratches and dents

Authenticity
Realistic textures create the illusion of real wood without the performance trade-offs.

Moisture resistant
TFL provides a performance surface that holds up for quick and easy cleaning.

Engineered and produced in the U.S.A.

Everyday Applications
Kitchens, Pantries, Closets, Laundry Rooms, Garages, Craft Rooms, Nurseries and More

Standards & Certifications
- EPA Formaldehyde Emission Regulation
- TSCA Title VI compliant
- CPA EC Sustainability Standard
- Carbon Neutral
- Produced using 100% pre-consumer recycled wood fiber

Maintenance
Clean with warm water and mild soaps only. Do not use cleaners with acids, alkalis or abrasives.

Handling & Storage
- Separate units with clean, dry spacers of uniform thickness. Use at least three spacers for panels up to 8' long and four or five for longer panels to prevent warping.
- Store indoors in a dry, clean, ventilated space.
- Avoid temperature and moisture extremes.
- Keep units off the floor to prevent moisture absorption.
- Separate units with clean, dry spacers of uniform thickness. Use at least three spacers for panels up to 8' long and four or five for longer panels to prevent warping.
- Allow panels to acclimate to the surrounding conditions for 72 hours before processing.
- Refer to CPA Technical Bulletin for shelving design and installation guidelines.

	Shelving	Closet Upright
Surface	TFL – Thermally-Fused Laminate	
Core	MDF, Particle Board, or EverPly™	
Edge profile	Square	
Edge treatment	Unfinished, Up to 4 sides edgebanded, UV finished [EverPly only] In .5, 1, 2, or 3mm	
Depth	8", 10", 12"	14"
Length	24", 36", 48"	24", 48", 72", 84"
Thickness	3/4" Pro Standard*	3/4" Pro Standard*
Pre-drilled	None	1 or 2-sided

*Also available in 1/2" and 5/8" depending on load rating, length of span and substrate.

FUNDER
BY GENESIS PRODUCTS

©2024 Genesis Products, Inc. GIW-241092 12/24

REQUEST YOUR SAMPLES TODAY

fundersales@genesisproductsinc.com
336.751.3501